



MATERIAL SAFETY DATA SHEET

SECTION 1 - PRODUCT INFORMATION

Product Name(s): Anionic emulsions including RS-1, RS-2, SS-1, SS1-H, CRO
Producer's Name: Granite Rock Company
Address: 350 Technology Dr., Watsonville, CA 95076
P.O. Box 50001, Watsonville, CA 95077-5001
Phone Number: (831) 768-2000
Date: October, 1999; Revised November, 2015

SECTION 2 - HAZARDOUS INGREDIENT(S)

Chemical Names	CAS Number	Quantity (Percent)	Formula	Exposure Limits in Air		
				ACGIH TLV TWA ⁽¹⁾	OSHA PEL ⁽²⁾	NIOSH REL ⁽³⁾
Petroleum distillate (asphalt)	8052-42-4	55-65	various	0.5 mg/m ³ (as fumes)	--	--
Sodium hydroxide	1310-73-2	< 1	NaOH	2 mg/m ³	2 mg/m ³	--
Hydrogen sulfide	7783-06-4	< 1	H ₂ S	10 ppm	20 ppm	--

(1) ACGIH TLV: American Conference of Industrial Hygienist Threshold Limit Value (TLV) time-weighted average (TWA).

(2) OSHA PEL: Occupational Safety and Health Administration Permissible Exposure Limit for an 8-hour time weighted average.

(3) NIOSH REL: National Institute for Occupational Safety & Health, Recommended Exposure Limit

SECTION 3 - HAZARD IDENTIFICATION

Overview: Anionic emulsions are a proprietary mixture containing water, emulsifiers, and asphalt binder(s).

Potential Health Effects

Eye Contact: Direct contact may cause redness, irritation, and burning. Repeated or prolonged exposure may cause conjunctivitis.

Skin Contact: Direct contact with asphalt dust may also cause skin irritation. Long term exposure may lead to irritation, dermatitis, and acne-like lesions.

Ingestion: May cause nausea, gastrointestinal irritation and vomiting.

Inhalation: Fumes may irritate the nose, throat, and respiratory tract. Coughing, sneezing, chest pain, shortness of breath, inflammation of mucous membrane, and flu-like fever may occur following exposures in excess of appropriate exposure limits. If hydrogen sulfide is present at high concentrations, exposure may cause convulsions, coma, and death.

Anionic emulsions (including RS-1, RS-2, SS-1, SS1-H)

SECTION 4 – FIRST-AID MEASURES

Eye contact: Immediately flush with plenty of water for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION.

Skin contact: Immediately WASH WITH SOAP AND LARGE AMOUNTS OF WATER for at least 15 minutes. Clean skin with waterless hand cleaner. Seek medical aid if irritation persists or develops.

Inhalation: Remove from exposure. Seek medical aid if respiratory difficulty persists or develops.

Swallowed: SEEK MEDICAL AID. Do not induce vomiting.

SECTION 5 - FIRE AND EXPLOSION

Extinguishing media: Agents approved for Class B fires (e.g., CO₂, dry chemical, or foam, water fog).

Special Fire Fighting Procedures: Use NIOSH/MSHA approved SCBA and full protective equipment.

Unusual Fire/Explosion Hazard: If hydrogen sulfide is present in sufficient quantities, flammable limits can increase to 4-45% by volume and pyrophoric iron compounds can be formed. In this case, use self-contained breathing apparatus (SCBA) in the pressure demand mode.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Spill Response Procedures: Remove all heat and ignition sources and increase ventilation. Use water vapor to reduce airborne vapors. For small spills, use sand or absorbent to capture. Place in sealed containers for disposal.

Preparing Waste for Disposal: Disposal must be in accordance with applicable federal, state, and local regulations. Enclosed-controlled incineration recommended, depending on jurisdiction.

SECTION 7 – EXPOSURE CONTROL & PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: None needed at ambient temperatures. If present in high vapors concentrations or TLV is exceeded, use NIOSH/MSHA approved supplied-air respirator.

Eye Protection: Safety glasses with side shields should be worn at all times.

Gloves: Nitrobutyl rubber or neoprene.

Other Clothing: Long sleeves.

Work Practices: Do not smoke.

Hygiene Practices: Wash exposed skin with soap and water.

SECTION 8 - HANDLING AND STORAGE

Protective Measures During Maintenance of Contaminated Equipment: No special measures required

Storage: Keep adequate ventilation in outside storage. Hydrogen sulfide gas may accumulate in storage tanks and bulk transport compartments containing asphalts.

SECTION 9 - PHYSICAL PROPERTIES

Vapor density (air=1):	N/A	Melting point:	N/A
Specific gravity:	1.0 – 1.04	Boiling point:	Approx 100C
Solubility in water:	unknown	Evaporation rate:	Negligible
Vapor pressure:	<0.1		
Appearance and odor:	Brown liquid, detergent odor		

SECTION 10 - STABILITY AND REACTIVITY

Reactivity: Material is stable and will not polymerize. May react with strong oxidizing agents such as chlorates, nitrates and peroxides. At room temperature, hydrogen sulfide may be given off.

Materials/Conditions to Avoid: High temperature heating.

Hazardous Decomposition Products: Heating this material may produce hydrogen sulfide.

GRANITE ROCK COMPANY DISCLAIMER

The information contained in this MSDS is based on tests, experience and other information which Granite Rock Company believes reliable and is supplied for informational purposes only. Since conditions of use are outside of our control, Granite Rock Company disclaims any liability for damage or injury which results from use of the above information. Nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability) or representation (including freedom from patent liability) by Granite Rock Company with respect to the information, the material described, or its use for any specific purpose, even if that purpose is known to Granite Rock Company.

Anionic emulsions (including RS-1, RS-2, SS-1, SS1-H)