

Section 1: Identification of product / manufacturer / utilization

Product form: Slurry

Product name: GraniteCoat Pavement Sealer, GraniterCoat Crack Sealer 1, GraniteCoat Crack Sealer 2, Bumper Adhesive, Loop Filler, Cold Pour Crack Filler, Blacktop, Sealer, Seal Coat

Synonyms: Anionic Asphalt Emulsion

Distributor

Granite Rock Company
350 Technology Drive
Watsonville, CA 95076

Phone: 831.768.2000
Emergency Phone: 888.762.5100

Section 2: Hazards identification

Classification of mixture:

- Eye Irritant – Category 2A
- Skin Corrosion/Irritation – Category 2
- Respiratory/Skin Sensitizer – Category 1



Signal word: WARNING

Hazard Statements:

- May cause skin and eye irritation.
- Vomiting may occur if swallowed.
- Substance may be harmful if swallowed irritating mouth, throat and / or stomach

- Fumes from heated material may be irritating.
- Prolonged or excessive inhalation may cause respiratory tract irritation.
- Vapors may have a strong offensive odor which may cause headaches, nausea and vomiting.
- Symptoms of overexposure include: fatigue, tearing of eyes, burning sensation in the throat, cough, and chest discomfort and skin irritation.

Precautionary Statements:

- Obtain and read product data sheet for instructions of use
- Do not handle material until all the safety data sheet has been obtain, read and understood.
- Contact with hot material may cause thermal burns

Prevention

- Do not eat, drink or smoke when using this product
- Do not breathe fume/gas/mist/vapors/spray
- Wear protective gloves/protective clothing/eye protection/face protection
- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood

Response

- If swallowed: Rinse mouth. DO NOT induce vomiting. Immediately call a poison center/doctor
- If on skin or hair: take off immediately all contaminated clothing. Rinse skin with water/shower.
- If inhaled: Remove person to fresh air and keep comfortable for breathing
- If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
- Continue rinsing. Immediately call a poison center/ doctor

GHS pictogram**Storage**

- Store in an appropriate container or containment structure

Disposal

- Dispose of contents/container in accordance with local/regional/national regulations

Section 3: Composition / Information on Ingredients

Chemical Name Number	Amount	CAS
Asphalt (Petroleum)	40 - 70 %	8052-42-4
Water	< 50%	7732-18-5
Sodium Hydroxide	< 0.5%	1310-73-2
Hydrogen Sulfide	< 0.5%	7783-06-4
Emulsifier (Confidential Ingredient A)	< 3.0%	TRADE SECRET
Quartz (SiO ₂)	0.0 – 20%	14808-60-7
Cellulose	0.0 – 5.0%	9004-34-6
Limestone	0.0 – 10.0%	1317-65-3
Feldspar-Group Minerals	0.0 – 30.0%	68476-25-5
Silica, Amorphous	0.0 – 60.0%	61790-53-2
Carbon Black	0.0 – 2.0%	1333-86-4
Latex	10.0 – 20.0%	25067-01-0

Component Information/Information on Non-Hazardous Components**General Information**

Concentration values are typical and may vary. Although specific identities of some products components are being withheld as trade secrets, known pertinent hazard are addressed in individual SDS.

Section 4: First Aid Measures**GENERAL FIRST AID MEASURES:**

Product is water soluble, rinse off immediately with soap and water. If solidified, treat as neat asphalt.

EYE CONTACT FIRST AID:

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.

SKIN CONTACT FIRST AID:

Wash skin with soap and water. Wear protective gloves to minimize skin contamination. If material is solidified use appropriate cleaner and wash from the skin.

INHALATION FIRST AID:

Although this product is not known to cause respiratory problems if breathing is difficult, safely remove victim to fresh air and provide oxygen. Get immediate medical attention.

INGESTION FIRST AID:

Get immediate medical attention. DO NOT induce vomiting due to danger of aspirating liquid into lungs. Gastric lavage may be required.

Section 5: Fire Fighting Measures**EXTINGUISHING MEDIA****SPECIAL HAZARDS:**

Fire Hazard: Product is an aqueous solution. Heated product may produce hazardous fumes, decomposition products or residues. Small quantities of hydrogen sulfide may be release upon heating.

Explosion Hazard: None

Reactivity:	Avoid contact with strong bases
Advice for Firefighters:	Decomposition may produce fumes, smoke, oxides of carbon and hydrocarbons and possible small quantities of hydrogen sulfide. Avoid breathing vapors from heated material. Combustion may produce CO, NO _x , SO _x and reactive hydrocarbons
Protection for firefighting:	As in any fire, wear self-contained breathing apparatus pressure-demand MSHA/NIOSH approved and full protective gear

Section 6: Accidental Release Measures

General measures:	Clean up spills immediately using appropriate personal protective equipment.
Non-emergency personnel:	
Protective equipment:	Glove, safety glasses, boots.
Emergency procedures:	Absorb spills with absorbent material or sand.
For emergency responders:	
Protective equipment:	Gloves, safety glasses, boots
Emergency procedures:	Stop the source of the release. Clean up release as soon as possible.
Environmental precaution:	Prevent contamination of soil, surface water or groundwater
Method for containment/clean up:	Absorb spills with absorbent materials. Contain spilled liquid with sand or earth. Contain liquid to prevent contamination of soil, surface water or groundwater. Large spillage would be dammed-off and pumped into containers. Prevent materials from entering streams, drainages or sewers.

Section 7: Handling and Storage
--

Shelf life:	6 months day @ 40°C (in original, sealed containers)
Additional Hazard:	When handling material, use protective clothing impervious to this material.
Safe Handling:	Use good hygiene measure: wash exposed areas with mild soap and water before eating, drinking or smoking and again when leaving work.
Storage conditions:	Do not store at temperatures above 40°C
Additional handling:	When sampling containers use appropriate personal protective equipment such as gloves, safety glasses, work boots and appropriate clothing. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

Sections 8: Exposure Controls / Personal Protections

Engineering measures:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.	
Eye/Face protection:	Where contact with this material is likely, eye protection is recommended.	
Skin protection:	Selection of specific items such as gloves, boots, apron or full body suit will depend on operation and potential exposure.	
Respiratory Protection:	Where there is potential for airborne exposure in excess of applicable limit, wear NIOSH/MSHA approved respiratory protection.	
Exposure Guidelines:		
Sodium Hydroxide:	OSHA PEL	10ppm mg/m ³
	OSHA PEL Ceiling Limit	2mg/m ³
Hydrogen Sulfide:	OSHA TWA	10ppm, 14mg/m ³
	OSHA STEL	15ppm
Carbon Black:	OSHA PEL	3.5 mg/m ³
	OSHA TWA	3.5 mg/m ³

Sections 9: Physical and chemical properties**Information of basic physical and chemical properties**

Physical state:	Slurry
Appearance:	Brown to Black
Odor:	Asphalt odor
pH	8-11
Melting point:	0°C
Freezing point:	0°C
Specific gravity:	2.0-2.7(water = 1)
Boiling point:	100°C @ 7600mm Hg
Flash point	None
UEL:	N/A
LEL:	N/A
Vapor pressure:	Same as water mmHg @21°C

Vapor density at 21°C	Same as water (air = 1)
Solubility:	Dispersible
%Volatiles:	<30% @21°C @ 760b mmHg
VOC:	<2%

Section 10: Stability and Reactivity

Reactivity: Low

Chemical stability: This compound is stable at ambient conditions.

Conditions to avoid: Avoid extreme high temperatures

Possibility of hazardous reactions: Low

Hazardous decomposition products: Decomposition will not occur if handled and stored properly

Incompatible materials: Avoid contact with strong bases.

Section 11: Toxicological Information

Skin corrosion: May cause irritation and a rash with prolonged or repeated contact with skin

Serious eye damage: Irritating, may injure eye tissue if not removed promptly.

Respiratory or skin sensitization: Repeated contact may cause skin irritation; prolonged inhalation may cause respiratory tract irritation

Germ cell mutagenicity: None

Reproductive toxicity: This product contains one or more chemicals known to cause reproductive harm.

Specific target organ toxicity (single exposure): Skin and or respiratory irritation, mild

Specific target organ toxicity (repeated exposure): Skin, respiratory, kidney and liver

Aspiration hazard: Respiratory distress as a result of aspiration

Symptoms after inhalation: Respiratory tract irritation, cough, chest discomfort

Symptoms after eye contact: Eye Tearing, irritation burns if contact made with heated material

Symptoms after ingestions: Harmful if swallowed, irritating to mouth, throat and stomach

Section 12: Ecological Information**Environmental Hazards**

This material should be prevented from uncontrolled applications to soil or earth. This material should be prevented from entering storm water, sewage drainage system and bodies of water.

Section 13: Disposal Consideration***Waste Disposal Instructions***

This product, as supplied, when discarded or disposed of, may be a hazardous waste according to Federal regulations (40 CFR 261). Under the Resource Recovery Act (RCRA), it is the responsibility of the user of the product to determine whether the material is a hazardous waste subject to RCRA. Treat or dispose of waste material in accordance with all local, state/provincial and national requirements. Avoid disposal into wastewater treatment facilities.

Disposal of Contaminated Containers or Packaging

Unclean empty containers should be disposed of in the same manner as the contents.

Contaminated Materials

Treat as product waste.

Section 14: Transport Information

<i>Product label:</i>	Overkote Pavement Sealer, Overkote Crack Sealer 1, Overkote Crack Sealer 2, Bumper Adhesive, Loop Filler, Cold Pour Crack Filler, Blacktop, Sealer, Seal Coat
<i>UN Number:</i>	Non-hazardous, no UN number
<i>DOT Shipping Name:</i>	Non Regulated, Water Based Asphalt Emulsion
<i>DOT Hazard Class:</i>	Non-hazardous

Section 15: Regulatory Information

EEC Symbols and Indications of Danger: Irritant (Xi)

WHMIS Hazard symbols: none

California Proposition 65: This product contains one or more chemicals known to the State of California to cause cancer and or reproductive harm.

Title V: Hydrogen sulfide (7783-06-4)

CERCLA Hazardous sub: Sodium Hydroxide (1310-73-2) RQ 1000 lb
 Hydrogen Sulfide (7783-06-4) RQ 100 lb

SC Toxic Air Pollutants List: Sodium Hydroxide (1310-73-2) RQ 1000 lb
 Hydrogen sulfide (7783-06-4) RQ 100 lb

Canadian Disclosure: Quartz (SiO₂) (14808-60-7)
 Carbon Black (1333-86-4)

TSCA Inventory Status: All ingredients of the product are listed.

Section 16: Other Information

Hazardous Material Information System (HMIS):	Health	1
	Flammability	1
	Physical Hazard	
	Personal Protection	B

NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme
 Protective Equipment: Safety glasses, gloves, respirator

Key/Legend

EPA – Environmental Protection Agency; TSCA = Toxic Substance Control Act: ACGIH

=

American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute of Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration, CERCLA = Comprehensive Environmental Response Compensation & Liability Act of 1980

The information contained in this SDS is based on tests, experience and other information that Granite Rock Company believes reliable and is supplied for informational purposes only. Since conditions of use are outside of our control, Granite Rock Company disclaims any liability for damage or injury which results from use of the above information. Nothing contained herein shall constitute a guarantee, warranty (including warranty of merchantability) or representation (including freedom from patent liability) by Granite Rock Company with respect to the information, the material described, or its use for any specific purpose, even if that purpose is known to Granite Rock Company.